



NOTES 1:

UL Standard :

- 1.Rating: 300V 15A
- 2.Insulation Withstands Voltage:  
AC 2000 V at 1 minute
- 3.Using Temperature Range:  
-40°C~+115°C
- 4.Suitable Electric Wire: 14~26 AWG

IEC Standard :

- 1.Rate Impulse Voltage: 6000V
- 2.Insulation Resistance:  
500MΩ or more at DC500V

NOTES 2:

1. RoHS Compliance.
- 2.Assemble 2P,only need one  
0134-1001 and one 0134-3002  
and one 0134C20200,0134C30200
- 3.Strip Length:10mm

5	COVER2	PA66	UL94-V0 GREY
4	COVER1	PA66	UL94-V0 GREY
3	0134-3001		GREY
2	0134-3002		GREY
1	0134-1001		GREY
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

DWG.	H.fan	DATE	2016.12.29	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	3:1 ( : )		
APP.		DATE		NAME	0134-33XX		
REV.	CONTENT	NAME	DATE	DINKLE ENTERPRISE CO.,LTD	DWG NO.	SP-03-013433XX	

△6			
REV.	CONTENT	NAME	DATE