



NOTES 1:  
 UL Standard :  
 1.Rating: 300V 15A  
 2.Insulation Withstands Voltage:  
 AC 2000V at 1 minute  
 3.Using Temperature Range:  
 -40°C~+115°C

IEC Standard:  
 1. Rate Impulse Voltage: 4000V  
 2.Insulation Resistance:  
 500MΩ or more at DC500V  
 NOTES 2:  
 1.RoHS compliance

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

ITEM	NAME OF PART	MATERIAL	NOTES
2	SOLDER PIN	COPPER ALLOY	Tin Plated
1	HOUSING	PA66	UL94-V0 GREY

DWG.	H.fan	DATE	16.12.06	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	5:1 ( : )		
APP.		DATE		NAME	0135-11XX		
				DWG NO.	SP-03-013511XX		

REV.	CONTENT	NAME	DATE
3			