0135-30



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3002
:	:
:	:
12	0135-3012

0135-31



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3102
:	:
:	:
12	0135-3112

0135-34



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3402
:	:
:	:
12	0135-3412

0135-35



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3502
:	:
:	:
12	0135-3512

0135-36



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3602
:	:
:	:
12	0135-3612

0135-37



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3702
:	:
:	:
12	0135-3712

0135-38



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3802
:	:
:	:
12	0135-3812



0135-39



Pitch:7.50mm

Approval	
Technical Data	UL / IEC
Rated voltage	300V / 450V
Rated current	15A / 12A
Conductor cross-section, solid (AWG/mm²)	
Conductor cross-section, flexible (AWG/mm²)	
Rated impulse voltage	6KV
Torque(N-m)	
Screw	
Wire strip length	

Pole	Cat.No.
02	0135-3902
:	:
:	:
12	0135-3912