





Approval		
		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm²)		
Conductor cross-section, flexible (AWG/mm²)		
Rated impulse voltage	6KV	
Torque(N-m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3002	
:	:	
:	:	
12	0135-3012	

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm ²)		
Conductor cross-section, flexible (AWG/mm ²)		
Rated impulse voltage	6KV	
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3102	
:	:	
:	:	
12	0135-3112	

		
Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm²)		
Conductor cross-section, flexible (AWG/mm²)		
Rated impulse voltage		6KV
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3402	
:	:	
:	:	
12	0135-3412	

		
Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm ²)		
Conductor cross-section, flexible (AWG/mm ²)		
Rated impulse voltage	6KV	
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3502	
:	:	
:	:	
12	0135-3512	



Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm ²)		
Conductor cross-section, flexible (AWG/mm ²)		
Rated impulse voltage	6KV	
Torque(N-m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3602	
:	:	
:	:	
12	0135-3612	

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm ²)		
Conductor cross-section, flexible (AWG/mm ²)		
Rated impulse voltage	6KV	
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3702	
:	:	
:	:	
12	0135-3712	

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm ²)		
Conductor cross-section, flexible (AWG/mm ²)		
Rated impulse voltage	6KV	
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3802	
:	:	
:	:	
12	0135-3812	

Approval		
		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	12A
Conductor cross-section, solid (AWG/mm²)		
Conductor cross-section, flexible (AWG/mm²)		
Rated impulse voltage	6KV	
Torque(N·m)		
Screw		
Wire strip length		
Pole	Cat.No.	
02	0135-3902	
:	:	
:	:	
12	0135-3912	