



Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

NOTES 1:

- UL Standard :
- Rating: 300V 10A
PITCH: 3.50mm
 - Insulation Withstands Voltage:
AC 2000V at 1 minute
 - Using Temperature Range:
-40°C~+110°C
 - Suitable Electric Wire: AWG 28~16

- IEC Standard :
- Rating: 160V 17.5A
 - Rate Impulse Voltage: 2500V
 - Insulation Resistance:
500MΩ or more at DC500V
 - Material Group : I
 - Pollution Degree : 2
 - Overvoltage Category: III
 - Using Temperature Range:
-40°C~+110°C
 - Suitable Electric Wire:
0.14~1.5mm²

NOTES 2:

- RoHS compliance
- Strip Length: 8~9mm
- Through hole reflow soldering
Temperature: 245°C

P	2	3	4	5	6	7	8	9	10	11	12	13
U	3.50	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50	42.00
V	7.70	11.20	14.70	18.20	21.70	25.20	28.70	32.20	35.70	39.20	42.70	46.20
P	14	15	16	17	18	19	20	21	22	23	24	
U	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50	
V	49.70	53.20	56.70	60.20	63.70	67.20	70.70	74.20	77.70	81.20	84.70	

3	LEVER	PA+GF	UL94-V0 WHITE
2	PIN+CLAMP		
1	HOUSING	PA+GF	UL94-V0 BLACK
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	ZTM	DATE	15.12.22	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	4:1 (:)		
APP.		DATE		NAME		0138-51XX	
				DINKLE ENTERPRISE CO.,LTD		DWG NO. SP-03-013851XX	

REV.	CONTENT	CHK.	DATE
------	---------	------	------