


未注公差/General tolerances(mm)											0.1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250		>315	>400
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50



5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn plated
3	Button	POM	UL94HB
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		300/8	/ 300/8
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		II/2	/ /
额定电压/电流/Rated Voltage(V)/Current(A)		250/8	/ /
额定脉冲电压(KV)/Rate Impulse Voltage(kV)		2.5	/ /
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)		28~16/0.2~1.0	
间距/Pitch(mm)/线数范围/Poles		3.50/N=02~22P	
剥线长度/Stripping length(mm)		10	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/		
APPD:	Li GL 2020.04.01		
CHKD:	Mao J 2020.04.01		
DRFT:	Wang LX 2020.04.01	NAME: 15EDGKN-3.5-XXP-1Y-1000A(H)	
DRAWING NO.: 15EDGKN-3.5-C08		REV	T0
TYPE: CUSTOMER DRAWING		SCALE: 2:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE

SIZE: A4 $\frac{mm}{inch}$