



NOTES:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 5.08mm, Poles : N=02~22P
- 3.Operating temperature: -40°C~+105°C
- 4.Undimensioned tolerances:

Pitch range in mm		Nominal dimension range in mm				- / /	
TO	Over	TO	Over	TO	Over	TO	Over
6	10	24	30	60	100	150	0.1/10
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30
							±2'

5.RoHS Compliance

2CDG - 5.08 - XXP - 1Y - 00A (H)
 (Series No.) (Pitch) (Poles) (Single Pitch) (Color): 1.(Grey) (RoHS) 2019.04
 00A--(Standard)



- 1.(Grey)
- 2.(Blue)
- 3.(Black)
- 4.(Green)
- 5.(Orange)
- 6.(Red)
- 7.(Transparent)
- 8.(Yellow)
- 9.(White)

1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

MATERIAL: /	SURFACE: /
MAT NO.: /	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
STATUS: /	
APPD: <i>Low CH 2019.8.27</i>	NAME: 2CDG-5.08-XXP-1Y-00A(H)
CHKD: <i>Jay.z 2019.8.27</i>	DRAWING NO.: 2CDG-5.08-C01
DRFT: MJN 2018.04.13	REV TO
SIZE: A4	TYPE: CUSTOMER DRAWING
SCALE: 1:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE