



| ITEM | PITCH RANGE |      | NOMINAL DIMENSION RANGE |      | TOLERANCE |
|------|-------------|------|-------------------------|------|-----------|
|      | TO          | OVER | TO                      | OVER |           |
| 6    | 10          | 10   | 30                      | 60   | ±0.10     |
| 10   | 10          | 24   | 30                      | 60   |           |
| 24   | 30          | 30   | 60                      | 100  | ±0.15     |
| 30   | 60          | 60   | 100                     | 150  |           |
| 60   | 100         | 100  | 150                     | 150  | ±0.20     |
| 100  | 150         | 150  | 150                     | 150  |           |
| 150  | 150         | 150  | 150                     | 150  | ±0.30     |
| 150  | 150         | 150  | 150                     | 150  |           |
| 150  | 150         | 150  | 150                     | 150  | ±0.50     |
| 150  | 150         | 150  | 150                     | 150  |           |
| 150  | 150         | 150  | 150                     | 150  | ±1.00     |
| 150  | 150         | 150  | 150                     | 150  |           |

- NOTES:
- 1.DIMENSION SHALL BE INTERPRETED PER ASME Y14.5-2009.
  - 2.PITCH: 5.0MM ,POLES: 02P
  - 3.RATED VOLTAGE/CURRENT: UL 300V/15A  
VDE 320V/20A
  - 4.OPERATION TEMPERATURES: -40℃~+105℃
  - 5.RATED IMPULSE VOLTAGE: 4.0KV
  - 6.INSULATION RESISTANCE: 5000MΩ/DC1000V
  - 7.UNDIMENSIONED TOLERANCES:

| REV | EGN     | DESCRIPTION      | DRFT      | DATE      |
|-----|---------|------------------|-----------|-----------|
| △   |         | 品名、料号增加环保标示“(H)” | LJH       | 12/11/07* |
| △   | 10-0017 | 增加UL刻字           | Jordan, Y | 02/11/10* |
| △   | 12-0015 | 更新图面             | Dick, H   | 02/11/12* |
| △   | 14-0102 | 增加VDE刻字,更改料号     | XL M      | 05/20/14* |



| DETACHED LISTS |       | ANGLES ± 1° |       | THIRD ANGLE PROJECTION    |           |
|----------------|-------|-------------|-------|---------------------------|-----------|
| X ±            | XXX ± | X ±         | XXX ± | DRG: Yangys               | 05/07/07  |
| XXX ±          | XXX ± | XXX ±       | XXX ± | CHKD: <i>pan oschling</i> | 5/21/14   |
| XXX ±          | XXX ± | XXX ±       | XXX ± | APPR: <i>pan oschling</i> | 5/21/14   |
| XXX ±          | XXX ± | XXX ±       | XXX ± | DO NOT SCALE DRAWING      | SCALE N/A |

| ITEM | NAME OF PART           | MATERIAL       | FINISH | PART NO.: |
|------|------------------------|----------------|--------|-----------|
| 3    | 2EDGRF-5.0 pin1        | 1090B00010(H)  | 1      | Copper    |
| 2    | 2EDGLF-5.0 pin2        | 1090B000080(H) | 1      | Copper    |
| 1    | 2EDGRF-5.0-02P-Housing | 1090A0Y02A(H)  | 1      | PA66      |

| NO. OF PART | Q'TY MATERIAL | NOTES |
|-------------|---------------|-------|
| 1           | 1             |       |

|              |                              |
|--------------|------------------------------|
| NAME:        | <b>DEGSON</b> 宁波高压电子有限公司     |
| DEGSON       | DEGSON ELECTRONICS CO., LTD. |
| TITLE:       | ASSEMBLY DRAWING             |
| DRAWING NO.: | 2EDGRF-5.0-E01               |
| REV          | T4                           |
| SHEET        | 1/1                          |