



△ A DD 0925 A M - 1 - H
 (1)(2) (3) (4)(5) (6) (7)

- (1) A:Adaptor Connector
- (2) DD:D-SUB To D-SUB
- (3) 0925:9 Pin To 25 Pin
- (4) A:Female To Male
- (5) M:Molding Type
- (6) 1:One Set/Bag
- (7) H:RoHS Compliant

P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
Shield	Shield

RoHS Compliant

④	UL1007 26AWG Insulator,Length 47mm(9Pcs),55mm(1Pcs)	10
	Molded PE Color Transparent	—
	Molded PVC Beige	—
③	Molded Thumbscrew #4-40,Length 21.5mm Beige	4
②	DB25 Male,Gold Flash On Contacts,Blue Insulator	1
①	DB9 Female,Gold Flash On Contacts,Blue Insulator	1
No.	Description	Q'ty

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE 0~200 ±10 201~1000 ±20					
PART No. △ ADD0925AM-1-H		MEI							
DRAWING No. ADD0925AM-1-H		HZF							
SCALE		REV.		B1		NO.REV.		REVISIONS	
NONE		REV.		B1		△ B1 Add P/N Code		HZF 08/03/2018	
						△ B0 Modify P/N:ADD0925EM-1-H-->ADD0925AM-1-H		HZF 02/18/2009	
						△ B0 NEW RELEASE		HZF 02/18/2009	
						NO.REV.		DATE	