



NOTES:

1. Insulation Withstands Voltage:
AC 2500V at 1 minute
2. Insulation Resistance:
500MΩ or more at DC500V
3. Using Temperature Range:
-40°C~+105°C
4. Suitable Electric Wire: AWG 28~10
5. RoHS compliance 0.2~4mm²

4	CLAMP	STEEL	Zn Plated
3	CONDUCTOR	COPPER-ALLOY	Tin Plated
2	CAGE CLAMP	SUS301 CSP-EH	
1	HOUSING	PA66	UL94-V0 YELLOW-GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Normal Geometric Tolerancing			
-	//	≡	⊥
0 to 100	0.2	0.3	0 to 10
over 100 to 150	0.3		over 10
over 150	0.5		0.2
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44

DWG.	Hgx	DATE	12.10.15	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	2.5:1 (:)	⊕ ⊞	
APP.		DATE		NAME		AK4-TR-PE	
REV.				DINKLE ENTERPRISE CO.,LTD		DWG NO. SP-03-AK4TRPE0	

REV.	CONTENT	CHK.	DATE