



Section A-A

SPECIFICATION
 Applicable: Battery CR2032
 ⚠ Insulator: LCP+30%G.F.(UL94V-0), White
 ⚠ Contact: Phosphor Bronze, Gold Flash Over All, Over Nickel
 RoHS Compliant

- BH 19 V W G - R5H - H
 (1) (2) (3) (4) (5) (6) (7)
- (1) BH: Battery Holder
 - (2) 19: CR2032
 - (3) V: SMT Straight
 - ⚠ (4) W: Insulator Color White
 - ⚠ (5) G: Gold Flash Over All, Over Nickel
 - (6) R5H: Tape & Reel 500 PCS/Reel
 - (7) H: RoHS Compliant

Recommended P.C.B. Layout

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.30 △.XX ±0.20 .XXX ±0.10 ANG. ±3°
PART No. BH19VWG-R5H-H		EMILY		
DRAWING No. BH19VWG-R5H-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		
REV.	B2	UNIT mm	⊕	

NO. REV.	REVISIONS	CHK	DATE
△ B2	Modify Data	HZF	03/31/2015
△ B1	Modify Data	HZF	11/22/2013
△ B0	NEW RELEASE	HZF	11/22/2011