



PCB LAYOUT

NOTES:

1. Rating: 500V 10A
2. Insulation Withstands Voltage: AC 2000V at 1 minute
3. Insulation Resistance: 500MΩ or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Value: 0.4N·m
6. Suitable Electric Wire: 24~12 AWG
7. BOM中的各料按以下各部分包裝出貨,如下:
 A. RAIL CLAMP及COVER組合包裝
 B. DEG-TB2P□
 C. SCREW
8. 將外殼的頭部、底部改爲噴砂面
9. RoHS compliance.

8	SCREW	STEEL	M2.6/Zn Plated
7	PCB		圖面標擬, 實際出貨不裝
6	MOUNTING RAIL		
5	MOUNTING RAIL		
4	MOUNTING RAIL		
3	COVER	PA66	UL94-V0 GREEN
2	DEG-TB2P□		
1	RAIL CLAMP	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

DWG.	Z.M.S	DATE	2018.05.08	UNITS	MM	SHEET/OF	1 / 1
CHK.	Siber.Ma	DATE	2018.05.08	SCALE	1.5:1 (:)		
APP.	Clark.Deng	DATE	2018.05.08	NAME		DEG-02P	
				DINKLE ENTERPRISE CO., LTD		DWG NO. SP-03-DEG02P00	

REV.	CONTENT	NAME	DATE