



NOTES 1:

UL Standard :

1. Rating: 500V 10A
2. Insulation Withstands Voltage: AC 2000V at 1 minute
3. Insulation Resistance: 500MΩ or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Value: 0.4N • m
6. Suitable Electric Wire: 24~12 AWG

7. EXTEND BOARD and COVER packaged together
8. RoHS Compliance
9. Height TS-35N: 70.0mm
Height TS-35/15N: 77.5mm
Height TS-32: 75.0mm

| Total Pitch Tolerances | | Normal Dimension Tolerances | |
|------------------------|-------|-----------------------------|-------|
| 0~30 | ±0.20 | 0~30 | ±0.25 |
| over 30~53 | ±0.25 | over 30~53 | ±0.30 |
| over 53~70 | ±0.30 | over 53~70 | ±0.35 |
| over 70~90 | ±0.35 | over 70~90 | ±0.44 |
| over 90~115 | ±0.44 | over 90~115 | ±0.55 |
| over 115~150 | ±0.55 | over 115~150 | ±0.70 |
| over 150~200 | ±0.70 | over 150~200 | ±0.85 |
| over 200~250 | ±0.85 | over 200~250 | ±1.00 |
| over 250~320 | ±1.00 | over 250~320 | ±1.20 |

| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|--------------|----------|----------------|
| 4 | SCREW | STEEL | M2.6/Zn Plated |
| 3 | COVER | PA66 | UL94-V0 GREEN |
| 2 | DEG-TB2P□ | | |
| 1 | EXTEND BOARD | PA66 | UL94-V0 GREEN |

| | | | | | | | |
|------|------------|------|------------|---------|----------------|----------|-------|
| DWG. | HX.Song | DATE | 2018.08.02 | UNITS | MM | SHEET/OF | 1 / 1 |
| CHK. | Hang.Han | DATE | 2018.08.02 | SCALE | 1.5:1 (:) | | |
| APP. | Clark.Deng | DATE | 2018.08.02 | NAME | DEG-04P | | |
| | | | | DWG NO. | SP-03-DEG04P00 | | |

| REV. | CONTENT | NAME | DATE |
|------|---------|------|------|
| 3 | | | |