



- NOTES: 1. Rating: 500V 10A
 2. Insulation Withstands Voltage: AC 2000V at 1 minute
 3. Insulation Resistance: 500M Ω or more at DC500V
 4. Using Temperature Range: -40°C~+105°C
 5. Screw Torque Value: 0.4N·m
 6. Suitable Electric Wire: 24~14 AWG
 7. RoHS compliance.
 8. BOM中的各料按以下各部分包裝出貨,如下:
 A. RAIL CLAMP及COVER組合包裝
 B. DEGH-TB3P
 C. SCREW
 9. 將外殼的頭部、底部改爲噴砂面

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2		0 to 10
over 100 to 150	0.3	0.3	over 10
over 150	0.5		0.3
Normal dimension Tolerances			
0~30	±0.25	over 70~90	±0.44
over 30~53	±0.30	over 90~115	±0.55
over 53~70	±0.35	over 115~150	±0.70

8	SCREW(自攻螺絲釘)	STEEL	M2.6x21(L)
7	PCB		模似件, 实际不裝
6	MOUNTING RAIL		
5	MOUNTING RAIL		
4	MOUNTING RAIL		
3	RAIL CLAMP	PA	UL94-V0 GREEN
2	DEGH-TB3P		GREEN
1	COVER	PA	UL94-V2 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	HJP	DATE	16.01.31	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1.5:1(1 : 1)		
APP.		DATE		NAME	DEGH-03P		
				DWG NO.	SP-03-DEGH03P0		

REV.	CONTENT	CHK.	DATE
△			