



PCB LAYOUT

NOTES:

1. Rating: 250V 12A
2. Insulation Withstands Voltage: AC 2000V/MIN
3. Insulation Resistance: 500MΩ or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. BOM中的各料按以下各部分包装出货, 如下:

6. 將外殼頭部、底部改成噴砂面
7. RoHS compliance.

- A. COVER1, COVER2, 及RAIL CLAMP 组合包装
- B. 2EHDR-4375
- C. SCREW
- D. HOUSING

ITEM	NAME OF PART	MATERIAL	NOTES
6	SCREW	STEEL	M2.6/Zn Plated
5	COVER1	PA66	GREEN
4	COVER2	PA66	GREEN
3	RAIL CLAMP	PA66	GREEN
2	HOUSING	PA66	GREEN
1	2EHDR-4375		GREEN

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

DWG.	ZDF	DATE	2019.05.23	UNITS	MM	SHEET/OF	1 / 1
CHK.	Siber.Ma	DATE	2019.05.23	SCALE	1.5:1 (1:1)		
APP.	Clark.Deng	DATE	2019.05.23	NAME		DEGM-12P	
				DINKLE ENTERPRISE CO., LTD.		DWG NO. SP-03-DEGM12P0	

REV.	CONTENT	NAME	DATE
3			