

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE

NOTES1:

UL Standard

- 1.Rated Voltage/Current : 300V / 7A
- 2.Torque Value : M2 , 1.77Lb.in
- 3.Wire Range : 24~18AWG

IEC Standard

- 1.Rated Voltage/Current : 130V / 10A
- 2.Torque Value : M2 , 0.2N.m
- 3.Wire Range : 0.5~1.0mm²

NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 3.5mm, Poles : N=02~24P
- 3.Stripping length : 5mm
- 4.Withstanding Voltage : AC1250V/1Min.
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm			
Over TO	Over TO	Over TO	Over TO	Over TO	Over TO
6 TO 10	10 TO 24	30 TO 60	60 TO 100	100 TO 150	150 TO 150
±0.15	±0.20	±0.30	±0.50	±0.70	±1.00
±0.15	±0.20	±0.30	±0.50	±0.70	±1.00

7.RoHS Compliance

文管中心
研发专用

2011.19

(仅限内部使用, 对外无效)

4	PIN	COPPER ALLOY	M2/Sn Plated
3	SCREW	STEEL	M2/Zn Plated
2	SPRING	STAINLESS STEEL	
1	HOUSING	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

PART NO.:
Series DG350-3.5宁波高松电子有限公司
DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD

APPD:

NAME:

CHKD:

DG350-3.5-XXP-1Y-00A(H)

DRFT:

Song 12/11/15

TITLE: CUSTOMER DRAWING

REV

TO

DRAWING NO.: DG350-3.5-C01

SHEET

1/1

MM
(INCH)

DO NOT SCALE DRAWING

SCALE

1:1

THIRD ANGLE PROJECTION

