







PCB LAYOUT



未注公差/General tolerances (mm)													0.1/10	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'



ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin header	Copper alloy	Sn Plated
3	Cage	Copper alloy	M2/Ni Plated
2	Screw	Steel	M2/Zn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage (V)/Current (A)	300/10	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage (V)/Current (A)	160/13.5	200/13.5	400/13.5
额定脉冲电压 (KV)/Rate Impulse Voltage (KV)	2.5	2.5	2.5
螺丝扭矩/Torque Tightening (N · m/Lb.in)	M2, 0.2/2		
线径范围 (硬线和软线)/Wire Range (rigid and flexible) (AWG/mm²)	30-16/ 0.2~1.0,1.5(sol)		
间距 Pitch (mm)/线数范围/Poles	3.5/N=02~24P		
剥线长度/Stripping length (mm)	5		
使用温度范围/Operating temperature (°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		

DG - series;
380 - model;
3.5 - pitch (mm);
XXP - number of poles;
1Y - color;
00A&Z(H) - internal code

APPD: 兰春华	2022.10.10
CHKD: 陈招	2022.10.10
DRFT: 袁路易	2022.10.10

MATERIAL: -	SURFACE/COLOR:	
MAT NO./REV: -	/ 00	MAT STATUS: 批量
NAME		
DG380-3.5-XXP-1Y-00A&Z(H)		
DRAWING NO. 200080101	TYPE CUSTOMER DRAWING	DRAWING STATUS 已发布
SCALE 2:1	SHEET 1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
00			袁路易	2022.10.10

Transfer or duplication of this document as well as the utilization or communication of its content are prohibited unless authorized in writing. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计注册外，其他内容均受法律保护。未经许可，不得复制或传播。本公司保留对涉及发明、实用新型及外观设计的所有权利。