



SPECIFICATION
 ▲ Insulator:ABS(UL94HB)
 Screw,Nut & SR:Steel,Nickel Plated
 Packing:1 Set/Bag
 RoHS Compliant

- ▲ $\frac{DHR}{(1)} \frac{37}{(2)} \frac{X}{(3)} \frac{T}{(4)} - \frac{1}{(5)} - \frac{H}{(6)}$
- (1) DHR:D-SUB Screw-On Hood Cable Outlet 45°
 - (2) 37:No. Of Position
 - (3) X:D-SUB Hood Insulator Color
 B:Beige
 C:Chromate Plated
 G:Gray
 K:Black
 - (4) T:With Thumbscrew
 - (5) 1:One Bag/Set
 - (6) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.5 .X ±0.3 .XX ±0.2 ANG. ±5°
PART No. DHR37XT-1-H		CHECKED BY HZF		
DRAWING No. DHR37XT-1-H		DRAWING BY SAN		
SCALE	NONE	REV.	A2	
UNIT mm				

NO.	REV.	REVISIONS	CHK	DATE
▲ A2		Modify Data	HZF	07/16/2014
▲ A1		Modify Data	HZF	12/10/2008
▲ A0		NEW RELEASE	HZF	02/07/2008