



NOTES 1:

UL Standard :

1. Insulation Withstands Voltage:
AC 2500V at 1 minute
2. Using Temperature Range:
-40°C~+105°C
3. Screw Torque Value: 1.2N·m
4. Suitable Electric Wire: AWG 20~8

IEC Standard:

1. Insulation Resistance:
500MΩ or more at DC1000V
2. Material Group : I
3. Pollution Degree : 3
4. Overvoltage Category: III
5. Using Temperature Range:
-40°C~+110°C
6. Screw Torque Value: 1.2N·m
7. Suitable Electric Wire: 0.2~6mm²

NOTES 2:

1. RoHS compliance
2. Strip Length: 14~16mm

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2	0.3	0 to 10
over 100 to 150	0.3		over 10
over 150	0.5		over 10
Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

5	CLAMP	STEEL	Zn Plated
4	WIRE CAGE	STEEL	Zn Plated
3	CONDUCTOR	COPPER ALLOY	Tin Plated
2	SCREW	STEEL	Zn Plated
1	HOUSING	PA	UL94-V0 YELLOW-GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	LJD	DATE	15.08.10	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	2:1 (:)		
APP.		DATE		NAME		DK6N-PE	
				DINKLE ENTERPRISE CO.,LTD		DWG NO. SP-03-DK6NPE00	

REV.	CONTENT	CHK.	DATE
1			