


 广东东菱电源科技有限公司 Guangdong DonePower Technology Co.,Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4

# 广东东菱电源科技有限公司


## 客户承认书

Guangdong Done Power Technology Co.,Ltd.

### SPECIFICATION

CUSTOMER			
MODEL NO.	DL-40H-LAN		
VERSION	V1.4		
SAMPLE DATE			
CUSTOMER			
TEST	CHECK	APPROVE	
Please return to us one copy of "SPECIFICATION FOR APPROVAL" with you approved signature.			
MANUFACTRUE			
EDIT	CHECK	APPROVE	
	 2021.03.23 08:13:13 +08'00'		数字签名者: 张鸿生 DN: cn=张鸿生, o, ou, email=978425630@qq.com, c=<无 日期: 2021.03.23 08:53:06 +08'00'
Guangdong Done Power Technology Co.,Ltd 广东东菱电源科技有限公司 No. 3-1&3-2, Kanglong 3rd Road, XinMao Industry Zone, Henglan Town, Zhongshan City, Guangdong Province, P. R. China Post code:528478 地址: 广东省中山市横栏镇新茂工业区康龙三路 3 号之一之二 邮编: 528478 TEL:0760-89838399 89838379 FAX:0760-89831157 89838396			



 广东东菱电源科技有限公司 Guangdong DonePower Technology Co., Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4

## FEATURES

- ◇ Class II driver power supply
- ◇ AC input: 220-240V ~ 50/60Hz
- ◇ The input is 230Vac, the output is full, and the efficiency is up to 89%
- ◇ PF > 0.95 & THD < 12% full load
- ◇ The level of lightning surge is differential mode L-N Class II + /-1 KV (2 ohm). Refer to IEC61000-4-5 2014
- ◇ CCC/TUV/CE/SAA approved
- ◇ Ultra-long life design, 5 years warranty



## TYPICAL APPLICATIONS


Commercial lighting , Household lighting



## MODEL LIST

Model	AC Input	Output voltage	Output current	Efficiency	THD	PF
				230Vac	230Vac	230Vac
DL-40H-C1050-LAN	220-240Vac 50/60Hz	25~42Vdc	1050mA	> 89%	< 12%	>0.95
DL-40H-C1000-LAN	220-240Vac 50/60Hz	25~42Vdc	1000mA	> 89%	< 12%	>0.95
DL-40H-C950-LAN	220-240Vac 50/60Hz	25~42Vdc	950mA	> 89%	< 12%	>0.95
DL-40H-C900-LAN	220-240Vac 50/60Hz	25~42Vdc	900mA	> 89%	< 12%	>0.95
DL-40H-C850-LAN	220-240Vac 50/60Hz	25~42Vdc	850mA	> 89%	< 12%	>0.95

Remark: Default tested at 230Vac, full load with 30 minutes, Ta: 25°C.

 广东东菱电源科技有限公司 Guangdong DonePower Technology Co., Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4


## ■ SPECIFICATION

### ◇ INPUT

Rated voltage	220 -240Vac
Voltage range	200 - 264Vac
Rated Frequency	50/60Hz
Power factor(PF)	@230Vac full load >0.95
Total harmonic distortion(THD)	@230Vac full load <12%
Input current	@230Vac full load 0.26A
Inrush current	@230Vac full load 60A

### ◇ OUTPUT

Model	DL-40H-C1050-LAN	DL-40H-C1000-LAN	DL-40H-C950-LAN	DL-40H-C900-LAN	DL-40H-C850-LAN
Rated current	1050mA	1000mA	950mA	900mA	850mA
Output current range	976-1102mA	930-1050mA	883-997mA	837-945mA	790-892mA
Output voltage range	25~42Vdc	25~42Vdc	25~42Vdc	25~42Vdc	25~42Vdc
Rated output power	44.1W	42W	39.9W	37.8W	35.7W
No load voltage	57V Max.	57V Max.	57V Max.	57V Max.	57V Max.
Efficiency	>89%@230Vac full load	>89%@230Vac full load	>89%@230Vac full load	>89%@230Vac full load	>89%@230Vac full load
Accuracy off output current	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%
Line regulation	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%
Load regulation	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%	-7%~+5%
Setup time	<500ms @ 230Vac	<500ms @ 230Vac	<500ms @ 230Vac	<500ms @ 230Vac	<500ms @ 230Vac

 广东东菱电源科技有限公司 Guangdong DonePower Technology Co., Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4

#### ◇ PROTECTION

Over load	Non-latching : Constant current limiting, recovers automatically after fault condition is removed.
Short	Hiccup and non-latching,:recover automatically after fault condition is removed.
Over voltage	hiccup or when it is at the highest point of output voltage the product would not be hurt when the fault is excluded or is start working again the power supply is working normally.

#### NOTE :

- 1) All parameters NOT specially mentioned are measured at 230VAC(50Hz) input, rated load and 25°C of ambient temperature.
- 2) Tolerance : includes set up tolerance, line regulation and load regulation.
- 3) Constant current operation region is within 50% ~100% rated output voltage. This is the suitable operation region for LED related applications.

#### ■ ENVIRONMENT

WORKING TEMP.	-25 ~ +50°C (Refer to "Derating Curve")
WORKING HUMIDITY	20 ~ 95% RH, non-condensing
STORAGE TEMP, HUMIDITY	-25 ~ +80°C, 10 ~ 95% RH
VIBRATION	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes
WITHSTAND VOLTAGE	I/P-O/P:3.75KVAC
ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C/ 70% RH
MTBF	470K hrs min. MIL-HDBK-217F (25°C)


#### ■ SAFETY & EMC

SAFETY	GB19510.1、GB19510.14、EN61347-1、EN61347-2-13、IEC61347-1、IEC61347-2-13、AS/NZS61347.1、AS/NZS61347.2.13 ; GB19510.1、GB19510.14、EN61347-1、EN61347-2-13、IEC61347-1、IEC61347-2-13、AS/NZS61347.1、AS/NZS61347.2.13 ;
EMC	EN 55015、EN 61000-3-2 、GB/T 17743、GB17625.1、 EN 61000-3-3
SUGER	L-N Class II +/- 1 KV ( 2 ohm ) (IEC61000-4-5 2014)
LEAKAGE CURRENT	<0.7mA /230Vac


#### NOTE :

The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.


### OUTPUT VOLTAGE VS PF




### OUTPUT VOLTAGE VS THD




### OUTPUT VOLTAGE VS EFFICIENCY




### LOAD DERATING CURVE




### INPUT VOLTAGE VS LOAD



### LIFE VS Tc




 广东东菱电源科技有限公司 Guangdong DonePower Technology Co., Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4


MECHANICAL SPECIFICATION & PACKING:

DIMENSION (mm)	135*40*25
PACKING	/

Case No. : FP04 Unit :mm



WEIGHT

 广东东菱电源科技有限公司 Guangdong DonePower Technology Co., Ltd 广东省中山市横栏镇康龙三路3号东菱工业园 咨询热线: 400-0760-585 WWW.DONEPOWER.COM.CN	产品类型	东菱 LED 室内驱动电源 DONE LED INTEGRATED SPECIAL DRIVER		
	产品系列	DL-40H-LAN	REV	1.4
Weight		100g/PCS		

**Warning:**

1. According to the certificate of power supply The LED driver of English nameplate is suitable for sale to Europe, America and India;
2. LED drivers for Chinese nameplates are only available for lamps sold to China.

