



FOR PCB LAYOUT

Normal Geometric Tolerancing				
	—	//	⊥	
0 to 100	0.2		0 to 10	0.2
over 100 to 150	0.3	0.3	over 10	0.3
over 150	0.5			
Total Pitch Tolerances		Normal dimension Tolerances		
0<U≤30	±0.20	0~30	±0.25	
30<U≤53	±0.25	over 30~53	±0.30	
53<U≤70	±0.30	over 53~70	±0.35	
70<U≤90	±0.35	over 70~90	±0.44	
90<U≤115	±0.44	over 90~115	±0.55	
115<U≤150	±0.55	over 115~150	±0.70	
150<U≤200	±0.70	over 150~200	±0.85	
200<U≤250	±0.85	over 200~250	±1.00	
250<U≤320	±1.00	over 250~320	±1.20	

NOTES:

- Rating: 150 V 8 A
- Insulation Withstands Voltage: AC 1600V at 1 minute
- Insulation Resistance: 500MΩ or more at DC500V
- Using Temperature Range: -40°C ~ +105°C
- Screw Torque Value: 0.4N·m
- Suitable Electric Wire: AWG 28~12

7.BOM中的料分五部分包裝出貨,如下:

- A.殼體DMEB-HT3P□□
- B.端子臺5EH-3PL
- C.端子臺5EH-3PR
- D.端子臺5ESDT-03P
- E.端子臺BS-110

8. RoHS compliance

ITEM	NAME OF PART	MATERIAL	NOTES
7	MOUNTING RAIL		模拟件
6	PCB		
5	BS-110	PA	UL94-V0 GREEN
4	5EH-3PR	PA	UL94-V0 GREEN
3	5EH-3PL	PA	UL94-V0 GREEN
2	5ESDT-03P	PA	UL94-V0 GREEN
1	DMEB-HT3P□□	PA	UL94-V0 GREEN

DWG.	ZW	DATE	2014.10.27	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1.5:1 ( : )	⊕	
APP.		DATE		NAME	DMEB-T3P□□		
REV.	CONTENT	CHK.	DATE	DINKLE ENTERPRISE CO., LTD	DWG NO.	SP-03-DMEBT3PO	