



Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

NOTES:

- Rating: 250 V 12 A
- Insulation Withstands Voltage: AC 1500V at 1 minute
- Insulation Resistance: 500M Ω or more at DC500V
- Using Temperature Range: -40°C ~ +105°C
- Screw Torque Value: 0.4N • m
- Suitable Electric Wire: AWG 28~12

7. BOM中的料分四部分包装出货, 如下:

- A. 上蓋CAP2
- B. 端子臺5ES-4PL
- C. 端子臺5ES-4PR
- D. 底座COVER3, COVER4, LOCKER  
CLAMP2, SPRING, CONDUCTOR組合包裝.

8. RoHS compliance

11	PCB	10、11号零件实际产品出货不装, 视图纯属模拟	
10	MOUNTING RAIL		
9	CONDUCTOR	COPPER ALLOY	Ni Plated
8	SPRING	SUS304	
7	CLAMP2	SPCC	Zn Plated
6	LOCKER	POM	ORANGE
5	5ES-4PR		
4	5ES-4PL		
3	CAP2	PA66	UL94-V0 GREEN
2	COVER4	PA66	UL94-V0 GREEN
1	COVER3	PA66	UL94-V0 GREEN

ITEM	NAME OF PART	MATERIAL	NOTES
------	--------------	----------	-------

DWG.	LJF	DATE	15.12.15	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1.5:1 ( : )		
APP.		DATE		NAME	DMEN-S4P□ □ -PE		
REV.	CONTENT	CHK.	DATE	DINKLE ENTERPRISE CO., LTD	DWG NO.	SP-03-DMENS4P0	



DINKLE

ENTERPRISE CO., LTD