



Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

NOTES:

- Rating: 250 V 12 A
- Insulation Withstands Voltage: AC 1500V at 1 minute
- Insulation Resistance: 500M Ω or more at DC500V
- Using Temperature Range: -40°C ~ +105°C
- Screw Torque Value: 0.4N · m
- Suitable Electric Wire: AWG 28~12

7. BOM中的料分四部分包裝出貨,如下:

- 上蓋CAP3
- 端子臺SES-3PL
- 端子臺SES-3PR
- 底座COVER5, COVER6, EXTEND BOARD, LOCKER及 CLAMP2, SPRING組合包裝.

8. RoHS compliance

ITEM	NAME OF PART	MATERIAL	NOTES
11	PCB	Not included	
10	MOUNING RAIL		
9	SPRING	SPRING STEEL	
8	CLAMP2	STEEL	Zn Plated
7	LOCKER	POM	ORANGE
6	SES-3PR		GREEN
5	SES-3PL		GREEN
4	CAP3	PA66	UL94-V0 GREEN
3	EXTEND BOARD	PA66	UL94-V0 GREEN
2	COVER6	PA66	UL94-V0 GREEN
1	COVER5	PA66	UL94-V0 GREEN

DWG.	LJF	DATE	16.12.15	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1.5:1 (:)		
APP.		DATE		NAME	DMEN-S6P □ □		
REV.	CONTENT	CHK.	DATE	DINKLE ENTERPRISE CO., LTD		DWG NO.	SP-03-DMENS6P0