



NOTES:

1. Rating: 250 V 12 A
2. Insulation Withstands Voltage:
AC 1500V at 1 minute
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range:
-40°C ~ +105°C
5. Screw Torque Value: 0.4N · m
6. Suitable Electric Wire: AWG 28~12

7. BOM中的料分五部分包装出货，如下：

- A. 上蓋CAP6
- B. 端子臺5EH-3PL
- C. 端子臺5EH-3PR
- D. 端子臺5ESDT-03P
- E. 底座COVER5, COVER6, LOCKER及
CLAMP2, SPRING組合包裝。
8. RoHS compliance

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

11	PCB	10, 11号零件实际产品出货不装， 图纯属模拟	
10	MOUNTING RAIL		
9	SPRING	SUS304	
8	CLAMP2	SPCC	Zn Plated
7	LOCKER	POM	ORANGE
6	5EH-3PR		GREEN
5	5EH-3PL		GREEN
4	5ESDT-3P		GREEN
3	CAP6	PA66	UL94-V0 GREEN
2	COVER6	PA66	UL94-V0 GREEN
1	COVER5	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	LJF	DATE	16.12.15	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1.5:1 (:)		
APP.		DATE		NAME	DMEN-T3P□□		
REV.		CONTENT	CHK.	DATE	DWG NO.	SP-03-DMENT3P0	



DINKLE

DINKLE ENTERPRISE CO., LTD