







REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 10/11/16'	~	

N=No. OF CONTACTS



RECOMMEND PCB LAYOUT(TOLERANCE= ± 0.05)

- NOTES:
- MATERIAL
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT: COPPER ALLOY.
 - SPECIFICATION
 - TEMPERATURE: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$.
 - CONTACT RESISTANCE:30m Ω max.
 - INSULATION RESISTANCE:100M Ω min.
 - DIELECTRIC WITHSTANDING VOLTAGE:AC 100V PER MINUTE.


3. PRODUCT NUMBER CODE:

DS1020-18- X X X X X X

- PACKING TYPE
 - B: Tube
 - R: Tape on reel(W/ Mylar)
- MYLAR SUPPORT
 - M: W/ Mylar
 - N: W/O Mylar
- CONTACT PLATING
 - 6: Tin
- COVER COLOR
 - B: Black
- HOUSING COLOR
 - V: Ivory
- No. OF CONTACTS
 - 04~40

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	± 0.60	X.	$\pm 5^{\circ}$
.X	± 0.38	.X	$\pm 3^{\circ}$
.XX	± 0.25	.XX	$\pm 2^{\circ}$
DRAWING TYPE		CUSTOMER	
SCALE		1:1	SHEET 1 OF 1
DRAWING NO.		C-DS1020-18-XXXXXX-A	

PROJECTION	TITLE
UNITS	1.0mm FPC
SHEET SIZE	ZIF V/T SMT TYPE H=5.5mm
	SERIES DS1020-18 SERIES

 晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD

Tel:86-574-63508787
Fax:86-574-62519917
E-mail:sales@connfly.com
http://www.connfly.com
Add: East Industry Zone KuangYan
Town Cixi Ningbo China
P.C:315333