



規格 Specifications

額定負荷 Ratings	DC12 V 1A
絶縁電阻 Insulation Resistance	DC 500V 60 Sec. 100 m Ω Min
抗電強度 Dielectric Voltage	AC 500V (50~60Hz) 60 Sec. Min
操作力 Operating Force	挿入力 (Insertion Force) 0.3 ~ 3.0 抜出力 (Extraction Force) 0.3~3.0
負荷壽命 Operating Life With Load	5,000 次 Cycles

Technical requirement :

1. This product should meet EU RoHS related requirement.
2. The surface of plastic part should be without any crackle such as burr,lack,and so on phenomenon.
3. The surface of metal part should be without any defect such as scaur,nick,oxidation and plating problem.
4. The electronic performance should be the same as spec.

Tolerances unless other wise spec.

Under 1.5 mm	±0.10
1.5 ~ 10.0 mm	± 0.20
Over 10.0 mm	± 0.25

No.	Parts	Materials	Q'ty	Remarks
5	Socket	Brass Strip	1	Ag Plated Ni Plated
4	Curve Pin	Brass Strip	1	Ag Plated Ni Plated
3	Curve Terminal	Brass Strip	1	Ag Plated Ni Plated
2	Contact Spring	Manganese Steel	1	Ag Plated Ni Plated
1	Housing	PBT	1	Black / Yellow

DCI DRAGON CITY INDUSTRIES LIMITED

Item Name	DC POWER JACK	Tolerance :
Item No.	DS-8022(SL)	Unit : mm

Design	K.W Law	Remark		Scale	
Drawing	W.K Yeung	Remark		Material	
Check	K.L Wong	Remark		Drawing No.	A508181500
Approval	K.W Chan	Remark		Sheet	