



1. Rating: —
PITCH: 6.10 mm
2. Insulation Withstands Voltage:
AC 2000 V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C ~ +105°C
5. RoHS Compliance

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

2	SOLDER PIN	COPPER ALLOY	Tin PLATED
1	HOUSING	PA66	UL94-V0 RED
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	Ao.Chen	DATE	2021.04.22	UNITS	MM	SHEET/OF	1 / 1
CHK.	Lj.Liang	DATE	2021.04.22	SCALE	6:1 (:)		
APP.	Clark.Deng	DATE	2021.04.22	NAME		DSS4N-XXP	
				DINKLE ENTERPRISE CO.,LTD		DWG NO. SP-03-DSS4NP00	

REV.	CONTENT	CHK.	DATE
△			