



- NOTES:
1. Rating: 300V 25A
PITCH: 9.50mm
 2. Insulation Withstands Voltage:
AC 2000V/MIN
 3. Insulation Resistance:
500M Ω or more at DC500V
 4. Using Temperature Range:
-40C~+105C
 5. Screw Torque Value: 13kgf-cm
 6. Suitable Electric Wire: AWG 22~12
 7. RoHS Compliance

Normal Geometric Tolerancing		≡	T
0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		

Total Pitch Tolerances		Normal dimension Tolerances	
0D≤30	±0.25	0~30	±0.25
30D≤53	±0.25	over 30~53	±0.30
53D≤70	±0.30	over 53~70	±0.35
70D≤90	±0.35	over 70~90	±0.44
90D≤115	±0.44	over 90~115	±0.55
115D≤150	±0.55	over 115~150	±0.70
150D≤200	±0.70	over 150~200	±0.85
200D≤250	±0.85	over 200~250	±1.00
250D≤320	±1.00	over 250~320	±1.20

P	2	3	4	5	6	7	8	9	10	11	12	13	14
U	9.50	19.0	28.5	38.0	47.5	57.0	66.5	76.0	85.5	95.0	104.5	114.0	123.5
V	38.0	47.5	57.0	66.5	76.0	85.5	95.0	104.5	114.0	123.5	133.0	142.5	152.0
P	15	16	17	18	19	20	21	22	23	24	25	26	
U	113.0	142.5	152.0	161.5	171.0	180.5	190.0	199.5	209.0	218.5	228.0	237.5	
V	161.5	171.0	180.5	190.0	199.5	209.0	218.5	228.0	237.5	247.0	256.5	266.0	

REV.	CONTENT	CHK.	DATE

DWG. CHK.	W	W	DATE	DATE
			09.12.07	

DWG. NO.	NAME	DWG. NO.
	DT-45-S02N-XX	

DINKLE
ENTERPRISE CO., LTD

ITEM	NAME OF PART	MATERIAL	NOTES
3	SCREW	STEEL	M3.5/Ni Plated
2	SOLDER POST	COPPER ALLOY	Tin Plated
1	HOUSING	PA66	UL94-V0 GREEN