



SPECIFICATION
 Current Rating: 2.5A AC/DC
 Voltage Rating: 250V AC/DC
 Temperature Range: -25°C~+85°C
 Contact Resistance: 10 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Withstanding Voltage: 800V AC/Minute
 △ Pin: Brass, Tin Plated
 △ Material: PA66(UL94V-0), Milk White
 RoHS Compliant

△ EH XX D - H
 (1) (2) (3) (4)

- (1) EH: 2.5mm EH Series
- (2) XX: No. of Position
- (3) D: Male DIP Straight
- (4) H: RoHS Compliant

Pin	A	B
02	2.50	7.50
03	5.00	10.00
04	7.50	12.50
05	10.00	15.00
06	12.50	17.50
07	15.00	20.00
08	17.50	22.50
09	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.25 .X* ±2° .XX ±0.20 .XX* ±1° .XXX ±0.10
PART No. EHXXD-H		MEI		
DRAWING No. EHXXD-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY HAO		
REV.	A3	UNIT mm	NO. REV. REVISIONS	

△ A3	Modify Data	HZF	05/04/2015
△ A2	Modify Data	HZF	12/06/2013
△ A1	Modify Spec.	HZF	05/19/2009
△ A0	NEW RELEASE	HZF	06/08/2006
NO. REV.	REVISIONS	CHK	DATE