

End-product drawing

REV.	DESCRIPTION	DESIGN	DATE
(X1)	NEW DRAWING	PDH	2019/10/10

NOTES:

1. MATERIAL: PA66、BRASS、 SILICONE;
2. CERTIFICATION: ROHS/cUL/TUV/SAA/CE;
3. FIRE-PROOT: UL94-V2。
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST: THE THREE ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY: 400V/24A
 B、 TEST VOLTAGE: 2500V
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-2.5mm²
 D、 OPERATING TEMPERATURE RANGE: -40~+105°C
 E、 PROTECTION CLASS: IP68

Factory: Xiamen Fucon IMP.&EXP. CO.,LTD


Waterproof connector (coupling for lighting) with screw brass clamps for three cables



3 Pins




Silicone parts



φA	Wire OD
φ11.5	φ9-12mm
φ8.5	φ5-9mm

Weight	MEAS	Each carton number	G. W.
67.1g	42*30*34cm	250pcs	17.6Kg

UNLABELED TOLERANCE			
X.	±0.35	X.XX	±0.20
X.°		X.°	±2°
X.X	±0.25	X.XXX	±0.10
X.X°		X.X°	±1°



UNITS	mm	DRAW	PDH	2019/10/10	PART NO.	EW-M20T-3P
SCALE	1:1	CHKD			DWG NO	
SHEET	1/1	APPD			TITLE	Waterproof connetor

FUCON