


A	1	2	3	4	5	6	7	8				
B	原材料		尼龙、硅胶、不锈钢						版本	说明	设计	日期
C	符合认证标准		SAA/TUV/RoHS/CE						A0	首次发布	MYJ	2022/5/10
D	阻燃等级		UL94 V-2									
E	防护等级		IP68									
F	额定电压		450 V									
A	耐电压		2500 V									
B	线材规格		0.5~6.0mm ²									
C	工作温度		-40~105 °C									
D	型号		夹线胶圈孔径(d)		适用线外径OD							
E	EW-M2068S-5T		A/B: φ 14mm		φ 10~14 mm							
F			A/B: φ 12mm		φ 9~12 mm							
A			A/B: φ 8.5mm		φ 5~9 mm							
B			C-E: φ 11.5mm		φ 9~12 mm							
C			C-E: φ 8.5mm		φ 5~9 mm							
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												
B												
C												
D												
E												
F												
A												