

1	2		3		4	5	6		7	8																																																																																							
未注公差/General tolerances(mm)					A	符号/SIGN	描述/DESCRIPTION		修订者/DRAWN	日期/DATE																																																																																							
>0	>3	>6	>10	>18		>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10	A	AD	新版发行		LHJ	2024/10/23																																																																												
3	6	10	18	30		50	80	120	180	250	315	400	500	>500	0.1/10																																																																																		
±0.15	±0.20	±0.25	±0.30	±0.35	±0.40	±0.50	±0.60	±0.80	±1.00	±1.20	±1.60	±2.00	±2.50	±3.00																																																																																			
<table border="1"> <tr> <td>③</td> <td>笼式弹簧 / Shrapnel</td> <td>SUS301</td> <td></td> <td>2</td> </tr> <tr> <td>②</td> <td>导电件 / Current Carrier</td> <td>T2</td> <td>镀雾锡 / Fogged Tin</td> <td>1</td> </tr> <tr> <td>①</td> <td>主座 / Housing</td> <td>PA66 UL94-V0</td> <td></td> <td>1</td> </tr> <tr> <td>ITEM 序号</td> <td>NAME OF PART 部件名称</td> <td>Material 材料</td> <td>NOTES 备注</td> <td>QTY 用量</td> </tr> </table>					③	笼式弹簧 / Shrapnel	SUS301		2	②	导电件 / Current Carrier	T2	镀雾锡 / Fogged Tin	1	①	主座 / Housing	PA66 UL94-V0		1	ITEM 序号	NAME OF PART 部件名称	Material 材料	NOTES 备注	QTY 用量		<p>技术参数 Technical parameter:</p> <table border="1"> <tr> <td>● 产品标准 / Rated Voltage</td> <td>UL1059</td> <td>IEC60947</td> <td>GB13140</td> <td>IEC60998</td> </tr> <tr> <td>● 获得安规及标志 Access to Safety Mark</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>● 证书号码 / Certificate No</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>● 额定电压 / Rated Voltage</td> <td>600V</td> <td>800V</td> <td></td> <td></td> </tr> <tr> <td>● 额定电流 / Rated Current</td> <td>30A</td> <td>32A</td> <td></td> <td></td> </tr> <tr> <td>● 线径范围 / Wire range</td> <td>28-10AWG</td> <td>0.2-4mm<sup>2</sup></td> <td></td> <td></td> </tr> <tr> <td>● 硬质导线 / Solid wire (AWG)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>● 软质导线 / Stranded wire (AWG)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>● 剥线长度 / Wire strip length</td> <td>10mm</td> <td>10mm</td> <td></td> <td></td> </tr> <tr> <td>● 绝缘耐压 / Withstanding Voltage</td> <td>2200V</td> <td>3500V</td> <td></td> <td></td> </tr> <tr> <td>● 温度范围 / Operating temperature</td> <td colspan="4">-40℃ ~ 105℃</td> </tr> <tr> <td>● 焊接温度 / Soldering temperature</td> <td colspan="4"></td> </tr> <tr> <td>● 关键尺寸 / Critical dimension</td> <td colspan="4">★</td> </tr> </table>					● 产品标准 / Rated Voltage	UL1059	IEC60947	GB13140	IEC60998	● 获得安规及标志 Access to Safety Mark					● 证书号码 / Certificate No					● 额定电压 / Rated Voltage	600V	800V			● 额定电流 / Rated Current	30A	32A			● 线径范围 / Wire range	28-10AWG	0.2-4mm <sup>2</sup>			● 硬质导线 / Solid wire (AWG)					● 软质导线 / Stranded wire (AWG)					● 剥线长度 / Wire strip length	10mm	10mm			● 绝缘耐压 / Withstanding Voltage	2200V	3500V			● 温度范围 / Operating temperature	-40℃ ~ 105℃				● 焊接温度 / Soldering temperature					● 关键尺寸 / Critical dimension	★					
③	笼式弹簧 / Shrapnel	SUS301		2																																																																																													
②	导电件 / Current Carrier	T2	镀雾锡 / Fogged Tin	1																																																																																													
①	主座 / Housing	PA66 UL94-V0		1																																																																																													
ITEM 序号	NAME OF PART 部件名称	Material 材料	NOTES 备注	QTY 用量																																																																																													
● 产品标准 / Rated Voltage	UL1059	IEC60947	GB13140	IEC60998																																																																																													
● 获得安规及标志 Access to Safety Mark																																																																																																	
● 证书号码 / Certificate No																																																																																																	
● 额定电压 / Rated Voltage	600V	800V																																																																																															
● 额定电流 / Rated Current	30A	32A																																																																																															
● 线径范围 / Wire range	28-10AWG	0.2-4mm <sup>2</sup>																																																																																															
● 硬质导线 / Solid wire (AWG)																																																																																																	
● 软质导线 / Stranded wire (AWG)																																																																																																	
● 剥线长度 / Wire strip length	10mm	10mm																																																																																															
● 绝缘耐压 / Withstanding Voltage	2200V	3500V																																																																																															
● 温度范围 / Operating temperature	-40℃ ~ 105℃																																																																																																
● 焊接温度 / Soldering temperature																																																																																																	
● 关键尺寸 / Critical dimension	★																																																																																																
<table border="1"> <tr> <td rowspan="3">FUCON</td> <td>CAT NO./认证型号</td> <td>FST4</td> <td>SHEET: 1/1</td> </tr> <tr> <td>PATE NO./成品料号</td> <td>02.09.011.0003</td> <td>SCALT: 1:1</td> </tr> <tr> <td>CUST NO./客户料号</td> <td>N/A</td> <td>REV: A0</td> </tr> <tr> <td>APPROVED/审核</td> <td>HYX 2024.10.23</td> <td colspan="2">MODEL: FST4</td> </tr> <tr> <td>CHECKED/核准</td> <td>CY 2024.10.23</td> <td colspan="2">DRAWING NO./图号: FST4-001</td> </tr> <tr> <td>DRAWN/制图</td> <td>LHJ 2024.10.23</td> <td colspan="2">TYPE/图纸类型: CUSTOMER_DRAWING</td> </tr> <tr> <td>SIZE: A4</td> <td>← 25mm (1 inch) →</td> <td colspan="2"></td> </tr> </table>					FUCON	CAT NO./认证型号	FST4	SHEET: 1/1	PATE NO./成品料号	02.09.011.0003	SCALT: 1:1	CUST NO./客户料号	N/A	REV: A0	APPROVED/审核	HYX 2024.10.23	MODEL: FST4		CHECKED/核准	CY 2024.10.23	DRAWING NO./图号: FST4-001		DRAWN/制图	LHJ 2024.10.23	TYPE/图纸类型: CUSTOMER_DRAWING		SIZE: A4	← 25mm (1 inch) →																																																																					
FUCON	CAT NO./认证型号	FST4	SHEET: 1/1																																																																																														
	PATE NO./成品料号	02.09.011.0003	SCALT: 1:1																																																																																														
	CUST NO./客户料号	N/A	REV: A0																																																																																														
APPROVED/审核	HYX 2024.10.23	MODEL: FST4																																																																																															
CHECKED/核准	CY 2024.10.23	DRAWING NO./图号: FST4-001																																																																																															
DRAWN/制图	LHJ 2024.10.23	TYPE/图纸类型: CUSTOMER_DRAWING																																																																																															
SIZE: A4	← 25mm (1 inch) →																																																																																																