

EMI FILTER

FWCMUU10 SERIES

ELECTRICAL CHARACTERISTICS:

Part No.	Inductance (Ω)Min	D.C.Resistance (Ω)Max	Rated current (A)
FWCMUU10V430L030C	43.0	3.50	0.30
FWCMUU10V300L040C	30.0	2.30	0.40
FWCMUU10V200L050C	20.0	1.50	0.50
FWCMUU10V150L060C	15.0	1.10	0.60
FWCMUU10V100L070C	10.0	0.80	0.70
FWCMUU10V074L080C	7.4	0.50	0.80
FWCMUU10V050L100C	5.0	0.35	1.00
FWCMUU10V035L120C	3.5	0.25	1.20
FWCMUU10V030L130C	3.0	0.20	1.30
FWCMUU10V022L150C	2.2	0.16	1.50
FWCMUU10V018L170C	1.8	0.13	1.70
FWCMUU10V015L200C	1.5	0.10	2.00
FWCMUU10V010L250C	1.0	0.08	2.50

FEATURES:

- Rated voltage (V): 85 to 265VAC, 50/60Hz
- Insulation resistance : 100MΩ MIN at 500DC.
- Turns Ratio : N1 : N2 = 1 : 1 ±2%
- Hi-Pot : Pri-Sec : 2500VAC/1mA/60Second
- Test Frequency Response : 10KHz 100mV.
- Operating temperature range: -40°C to +105°C
- Temperature Rise : 40°C MAX
- All parts meet RoHS compliance.

PHYSICAL CHARACTERISTICS TECHNICAL INFORMATION

