



Normal Geometric Tolerancing				
—	//	≡	⊥	
0 to 100	0.2	0.3	0 to 10	0.2
over 100 to 150	0.3		over 10	0.3
over 150	0.5			
Total Pitch Tolerances		Normal dimension Tolerances		
0<U<=30	±0.20	0~30	±0.25	
30<U<=53	±0.25	over 30~53	±0.30	
53<U<=70	±0.30	over 53~70	±0.35	
70<U<=90	±0.35	over 70~90	±0.44	
90<U<=115	±0.44	over 90~115	±0.55	
115<U<=150	±0.55	over 115~150	±0.70	
150<U<=200	±0.70	over 150~200	±0.85	
200<U<=250	±0.85	over 200~250	±1.00	
250<U<=320	±1.00	over 250~320	±1.20	

NOTE:  
1.RoHS Compliance.

1	KMLRML	PA66	GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	Hgx	DATE	11.06.22	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1.8:1 ( : )	⊕	
APP.		DATE		NAME KMLRML			
REV.				CONTENT	CHK.	DATE	DINKLE ENTERPRISE CO.,LTD
				DWG NO.		SP-03- KMLRML00	

△			
REV.	CONTENT	CHK.	DATE