



Model	Output Current	Input Current	Input Power	Output Power Range	PF	Efficiency	Output Voltage	No load Voltage
LC75W900-1800 DALI NFC	900-1500mA	≤0.42A	84.2W	18.00-75.00W	≥0.95	89%	20-50	60V
	1550-1800mA	≤0.52A	84.9W	31.00-75.60W	≥0.95		20-42	

\* Test result @230V, 50Hz, Full Load

### 1. Parameters












category	Item	Technical Norm
Features	Output Type	Constant Current
	Dimming Type	DALI-2 / Touch DIM
	Output current setting	Near field communication (NFC)
	Output Features	Isolation
	IP Grade	IP20
	Insulation Class	Class I
Input	Rated Input Voltage	220-240VAC
	Range of Input Voltage	198-264VAC
	Range of DC Input Voltage	180-280VDC
	Frequency	0/50/60Hz, Range:0/47-63Hz
	Input Current	≤0.52A max
	Input Power	≤84.9W max
	Power Factor	≥0.95 (230VAC, full load)
	THD	≤8.5% (230VAC, full load)
	Standby Power Consumption	≤0.45W @230VAC (DIM to off)
	Inrush Current	≤27A/16.8us (230VAC, full load)
	Connected quantity of 10A Breaker	7pcs/type A ; 12pcs/type B ; 19pcs/type C
Connected quantity of 16A Breaker	12pcs/type A ; 19pcs/type B ; 30pcs/type C	
Connected quantity of 20A Breaker	14pcs/type A ; 23pcs/type B ; 37pcs/type C	
Output	Output Voltage	20-50VDC@900-1500mA 20-42VDC@1550-1800mA
	No Load Voltage (Uout)	60VDC Max.
	Output Current	900-1800mA (by NFC setting ,Factory set current of 900mA)

Output	Max. Output Power	75.6W
	Efficiency	≥89% (230VAC, full load@max current)
	Output LF current ripple (< 120 Hz)	±3% ( $I_{max}-I_{min}$ ) / ( $I_{max}+I_{min}$ )
	Current Accuracy	±5%
	Output PstLM (at full load)	≤1
	Output SVM (at full load)	≤0.4
	Starting Time (AC mode)	≤0.8S (230VAC, full load, by DALI system)
	Starting Time (DC mode)	≤0.4S
	Switching over time (AC/DC)	≤0.4S
Control Method	Secondary PUSH dimming	Secondary PUSH dimming (Max. lead wire length: 20m, same port of DALI)
	PUSH-button	Max parallel connections qty for Push-dim 15
	DALI function	DALI dimming (Max. lead wire length: 300m) logarithm or linear dimming curve selectable
	Dimming range	DALI dimming: 1%-100%
	NFC current setting	The output current can be set within the total value range in 1-mA-steps. Output current is mean value. Setting is by KGP's software APP/APK/PC with FEIG equipment or mobile phone.
Protection	Short Circuit Protection	Auto Recovery
	Overload Protection	Auto Recovery (not be hot swap)
	No-load Protection	Auto Recovery
	Insulation voltage	3000V 5mA 60S between P-S, 1500V 5mA 60S between P-E
	Insulation resistance	>100M ohm @ 500VDC L/N to PE
	Leakage current	< 700μA, I/P to O/P or I/P to PE @230V input
Environment	Ta/Operation Temperature	-25....+50°C
	Ts/Storage Temperature	-25....+90°C
	Tc/Enclosure Temperature	90°C
	Humidity	10%....90%RH
	Atmosphere	86-108KPa
Construction	Connection Method	Push-in Terminal
	Installation	Build-in
	PRI Wire preparation	0.5-1.5 <sup>□</sup> / 8-9mm
	SEC Wire preparation	0.5-1.5 <sup>□</sup> / 8-9mm
	DALI Wire preparation	0.5-1.5 <sup>□</sup> / 8-9mm
	Dimension	280*29.4*21mm (L*W*H)
Standards	Certification	CE/ENEC/SAA/UKCA/CB
	Safety Standards	EN61347-1:2015/A1:2021; EN61347-2-13:2014/A1:2017; EN62384:2006/A1:2009; AS 61347.2.13:2018; AS/NZS61347.1:2016; BS EN61347-1:2015/A1:2021; BS EN61347-2-13:2014/A1:2017; IEC 61347-2-13:2014; IEC 61347-1:2015


	EMC Standards	AS/NZS CISPR 15:2011; AS CISPR 15:2017 ;
	Performance	EN 62384
	DALI performance	EN 62386-101 (DALI-2) EN 62386-102 (DALI-2) EN 62386-207 (DALI-2, including part 251, 252, 253)
	Surge	L-N/1KV (L/N)-PE/2KV
Others	RoHS	2011/65/EU
	Life Time	50000h Tc=90°C
		75000h Tc=85°C
100000h Tc=80°C		
	Warranty	5years , F.R. < 10000ppm

Remark: 1.All Parameters, if not specified, are measured at 230VAC/50Hz and 25°C ambient temperature.  
 2.LED Driver is a component of the luminaires, Luminaires and wire layout will affect the EMC, please check the EMC with end products again.  
 3.During the PUSH DIM test, the number of parallel connections must be less than 15PCS.

### 2. Label

<input type="checkbox"/> L <input type="checkbox"/> N <input type="checkbox"/> ⊕ <input type="checkbox"/> DA <input type="checkbox"/> DA	 <b>KGP</b> KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid	<b>LED Dimmable Driver</b> <b>LC75W900-1800 DALI NFC</b> Constant Current Type for LED Only Input Voltage:220-240VAC Input Frequency:0/50-60Hz Range of application DC 180-280V	•tc Power Factor:≥0.95 Iin:≤0.52A SEC:900-1800mA 20-50VDC Prange=18-75.6W Uout:60VDC Max.75.6W Tc:90°C Ta:50°C	       	 wire preparation 8-9mm PRI: 0.5-1.5° DALI: 0.5-1.5° SEC: 0.5-1.5°	<input type="checkbox"/> SEC + <input type="checkbox"/> SEC 1 <input type="checkbox"/> SEC 2 
--	---	---	--	---	--	---


### 3. Dimension (Unit: mm)




### 4. Installation / wiring

Circuit diagram


220-240 V  
0/50/60 Hz



220-240 V  
0/50/60 Hz



### 5. Output Power Window




### 6. DALI dimming curve

formula for DALI dimming.


$$X(n) = 10^{\left\{ \left[ \frac{(n-1)}{(253/3)} \right] - 1 \right\}}$$

Here, n means the target dimming stage of the total 254 stages.

X(n) means the percent of the maximum output current



### 7. Packing information




Carton L*W*H(mm)	Pcs/Carton	Net weight/ Pcs(kg)	Net weight/ Carton(kg)	Gross weight / Carton(kg)
325*303*240	80	0.165	13.20	14.52







### 8. NFC current setting:

NFC Reader (optional)

Feature:

Easily on-line read a output current from a driver or write a new current data to a driver throughout KGP NFC reader within few seconds.



Product	Description	Interface	Matching antenna	Zhaga approval	Usage
 ID CPR30+	Desktop programmer	USB	Integrated	Yes	Single Programming on Desktop
 ID ISC.PRH101-USB	Handheld programmer	USB	Integrated	Yes	Single Programming by Handheld
 ID ISC.MR102-USB	Middle range programmer, for connecting external antenna	USB	RF-MANT12786 	Yes	Single Programming on Product line
 ID ISC.LR1002-E	Long range programmer, for connecting external antenna	USB,RS232,TCP/IP	ID ISC.ANT310/310 	Yes	Multi Programming System

### APP NFC

**Feature:**

Quickly check output current of a LED driver simply via iPhone smart phone, as well as, correct or setup a new current data immediately with no extra equipment at any job site.

**ICON**



**Main**



**Download method**

1. Scan the QR code to download




2. On your iPhone, search for KGP NFC in APP Store to download it



iPhone smartphones with NFC can be downloaded and used directly

An iPhone smartphone without NFC requires the following devices to use it

Product	Description	Interface	Matching antenna	Zhaga approval	Usage
 ID ECCO Smart HF-BLE	Handheld wireless programmer	USB, Bluetooth LE V4.2 & V5.0	Integrated	Yes	Handheld programming, installation and maintenance work

### 9. Push Dim :

#### 9.1 On / off:

Short push (120ms-600ms) on the switch

Stepless dimming: long push (> 0.6sec) on the switch

#### 9.2 Power-on memory function

When the LED driver is powered on, it will restore the memory before the LED driver is powered off. (brightness remembers the brightness after the last dimming is stable, and the bright ness during dimming is not memorized)

### 9.3 Light on/off

If the light is on, the light will be off after a short press. If the light is off, the light will be on after a short press. The time range of short press is 120-600mS.

### 9.4 PUSH Dimming

Press and hold the push switch for a long time, the light will enter the dimming state, if the previous time is dimming, it will automatically turn to dimming the next time. After releasing the reset button, the dimming stops and the current illuminance is maintained. The dimming range is 1%-100%. The default is to dim when the power is first long-press. If the brightness of the power-on is the maximum brightness, the first long-press is to dim. (Long press 0.6-3S to start dimming.)

### 9.5 Forced synchronization

Long press for 10 seconds to turn on all the lights and turn on the same brightness (50%), and continue to quickly short press will not change. After a short period of time without short press operation, the module exits the synchronization mode, and the short press restores the switch function.

### 9.6 PUSH Dimming rate

Long press the push switch 10S to switch the dimming rate to 3S, Long press the push switch 20S to switch the dimming rate to 6S, and it can also be changed by MAGIC or production software.

## 10. REVISION HISTORY

Date	Revision	Remark
2023.11.02	V0.01	Modify fonts, add NFC content, update images, Packing information