



SPECIFICATION
 Current Rating:3.0 Amp
 Withstand Voltage:1000V AC/DC
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operation Temperature:-40°C~+105°C
 Insulator:PBT(UL94V-0)
 Contact:Brass,Gold Flash Over Nickel
 Metal Latch:Zinc Alloy,Nickel Plated
 No. Of Contact:08,10,14,16,20,26,30,34,40
 Contacts Are Toolled Already
 RoHS Compliant

LD XX - ML - H
 (1) (2) (3) (4)
 (1) LD:2.54mm Latch Header DIP Straight
 (2) XX:No. Of Position
 (3) ML:Metal Latch
 (4) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE					
PART No. LDXX-ML-H		MEI		X. ±0.25 X. ±2°					
DRAWING No. LDXX-ML-H		CHECKED BY HZF		.X ±0.20 .X ±1.5°					
SCALE NONE		DRAWING BY CYP		.XX ±0.15 .XX ±1°		A2	Modify Spec.	HZF	01/09/2018
REV. A2		REV. A2		.XXX ±0.10 .XXX ±0.5°		A1	Modify Dim.	HZF	08/31/2016
UNIT mm		UNIT mm		UNIT mm		A0	NEW RELEASE	HZF	11/07/2014
NO. REV.		NO. REV.		NO. REV.		REVISIONS		CHK	DATE