



△ SPECIFICATION

Current Rating:3 Amp
 Withstand Voltage:1000V AC
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operation Temperature:-40°C~+105°C
 Insulator:PBT(UL94V-0),Black
 Contact:Brass,Gold Flash Over Nickel
 Only 60P~64P With Slot "A"
 Less Than 18 Pin Without Slot "B"
 RoHS Compliant

L D XX S - H
 (1) (2) (3) (4) (5)

- (1) L:2.54mm Latch Header
- (2) D:DIP Straight
- (3) XX:No. Of Position
- (4) S:With Short Ejectors
- (5) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY	
PART No. LDXXS-H		MEI	
DRAWING No. LDXXS-H		CHECKED BY HZF	
SCALE NONE		DRAWING BY CYP	
REV.	A3	UNIT	mm

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			
△ X.	±0.25	X.*	±2°
.X	±0.20	.X*	±1.5°
.XX	±0.15	.XX*	±1°
.XXX	±0.10	.XXX*	±0.5°
NO.REV.	REVISIONS	CHK	DATE

△ A3	Modify Data	HZF	05/29/2015
△ A2	Modify Data	HZF	04/22/2015
△ A1	Modify Data	HZF	03/06/2014
△ A0	NEW RELEASE	HZF	05/16/2012