



**SPECIFICATION**

**1.General Characteristics**  
 3.0mm Micro Fit 1XXX Male  
 Housing Black Insulator

**2.Material&Finish**  
 Housing:PA66(UL94V-2),Black

**3.Electrical Characteristics**  
 Current Rating:5A AC,DC  
 Voltage Rating:250V AC,DC  
 Insulation Resistance:1000 Megaohms Min.  
 Withstand Voltage:1500V AC/Minute

**4.RoHS Compliant**

MIF 1 X XX PH - H  
 (1) (2) (3) (4) (5)

(1) MIF:3.0 Micro Fit  
 (2) 1:Single Row  
 (3) XX:No. Of Position/Per Row  
 (4) PH:Male Housing  
 (5) H:RoHS Compliant

Pin	A	B
2	3.00	6.85
3	6.00	9.85
4	9.00	12.85
5	12.00	15.85
6	15.00	18.85
7	18.00	21.85
8	21.00	24.85
9	24.00	27.85
10	27.00	30.85
11	30.00	33.85
12	33.00	36.85

**AUK** A MEMBER OF AUK GROUP  
**太聯事業股份有限公司**  
**AUK CONTRACTORS CO., LTD.**

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X $\pm 0.50$ .XX $\pm 0.25$ .XXX $\pm 0.10$ ANG. $\pm 2^\circ$
PART No. MIF1XXXPH-H		MEI		
DRAWING No. MIF1XXXPH-H		HZF		
SCALE		GAO		
NONE	REV.	A0	UNIT	mm

NO.	REV.	DESCRIPTION	CHK	DATE
△ A0		NEW RELEASE	HZF	08/01/2012
		REVISIONS		