



SPECIFICATION

1.General Characteristics
 3.0mm Micro-Fit Wafer 2XXX SMT 90°
 Fitting Nail:SMT Black Insulator Tin Plated
 Tape & Reel 250 PCS/Reel

2.Material&Finish
 Insulator:LCP(UL94V-0),Black
 Contact:Brass,Tin Plated

3.Electrical Characteristics
 Current Rating:5A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Withstand Voltage:1500V AC/Minute

4.Environmental Characteristics
 Temperature Range:-25°C~+85°C

5.RoHS Compliant

MIF $\frac{2}{(1)}$ X $\frac{XX}{(3)}$ $\frac{P}{(4)}$ $\frac{W}{(5)}$ - $\frac{R2H5}{(6)}$ - $\frac{H}{(7)}$

- (1) MIF:3.0mm Micro-Fit Series
- (2) 2: Dual Row
- (3) XX: No. Of Position/Per Row
- (4) P: Male
- (5) W: SMT Right Angle Fitting Nail: SMT
- (6) R2H5: Tape&Reel 250 PCS/Reel
- (7) H: RoHS Compliant

Pin	A	B	C
2	--	6.65	11.20
4	3.00	9.65	14.20
6	6.00	12.65	17.20
8	9.00	15.65	20.20
10	12.00	18.65	23.20
12	15.00	21.65	26.20
14	18.00	24.65	29.20
16	21.00	27.65	32.20
18	24.00	30.65	35.20
20	27.00	33.65	38.20
22	30.00	36.65	41.20
24	33.00	39.65	44.20



CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 .X ±0.25 .XX ±0.20 .XXX ±0.05 ANG. ±1°
PART No. MIF2XXXPW-R2H5-H		MEI		
DRAWING No. MIF2XXXPW-R2H5-H		HZF		
SCALE NONE		CYP		
REV.	A4	UNIT mm	NO. REV.	

A4	Modify P/N: MIF2XXXPW-R2H-H --> MIF2XXXPW-R2H5-H	HZF	05/20/2017
A3	Modify Data	HZF	12/20/2016
A2	Modify P/N: MIF2XXXPW-RXXX-H --> MIF2XXXPW-R2H-H	HZF	12/15/2014
A1	Modify Data	HZF	05/26/2014
A0	NEW RELEASE	HZF	06/23/2013
NO. REV.	REVISIONS	CHK	DATE