


## NL10276BC16-06

8.4" XGA

Industrial use

### [Features]

- Ultra-wide viewing angle(Super Fine TFT(SFT))
- High luminance (600cd/m<sup>2</sup>)
- High contrast (1,000:1)
- Wide color gamut (72%)
- 16.77M/262K colors (LVDS RGB 8-bit/6-bit)
- Reversible-scan direction
- Long-life LED backlight\*<sup>1</sup>



Pixel	1,024(H) x 768(V)
Display area	170.496(H) x 127.872(V)mm 8.4 inches (21cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.1665(H) x 0.1665(V) mm
Luminance	600cd/m <sup>2</sup> (typ.)
Contrast ratio	1,000:1 (typ.)
Viewing angle※ <sup>2</sup>	Up: 88°,Down: 88°,Left: 88°,Right: 88°
Response time※ <sup>3</sup>	25ms (typ.)
Signal system	LVDS 1 port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	5.6W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +80°C
Polarizer surface	Clear
Module size	200.0 (typ.) x 152.0 (typ.) x 8.7 (max.)mm
Weight	260g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	104PW03F

※1: 100k hours long life LED

※2: Contrast ratio ≥ 10:1

※3: Ton+Toff (10%←→90%)

※All information is subject to change without notice.

※Screen images are simulated.

<NLT Technologies web site>

Japanese <http://www.nlt-technologies.co.jp/jp>

English <http://www.nlt-technologies.co.jp/en>

Last update:11/2015

©NLT Technologies, Ltd. 2011-2015