

NL10276BC30-34R

15.0" XGA
Industrial use
[Features]

- **262K colors (LVDS RGB 6-bit)**
- **Long-life LED backlight^{※1}**



Pixel	1024(H) x 768(V)
Display area	304.128(H) x 228.096(V)mm 15.0 inches (38cm)
Display color	262,144 colors
Pixel pitch	0.297(H) x 0.297(V)mm
Luminance	400cd/m ² (typ.)
Contrast ratio	600:1 (typ.)
Viewing angle^{※2}	Up: 80°,Down: 80°,Left: 80°,Right: 80°
Response time^{※3}	18ms (typ.)
Signal system	LVDS 1-port RGB 6-bit
Power supply voltage	3.3V
Power consumption	9.8W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-20°C to +80°C
Polarizer surface	Antiglare
Module size	W 326.5 (typ.) x H 253.5 (typ.) x D 12.0 (max.)mm
Weight	970g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	150PW02F

※1 70k hours long life LED

※2: Contrast ratio ≥ 10:1

※3: Ton+Toff (10%←→90%)

※All information is subject to change without notice.

※Screen images are simulated.

< NLT Technologies web site >

Japanese <http://www.nlt-technologies.co.jp/jp>

English <http://www.nlt-technologies.co.jp/en>

Last update:12/2015

©NLT Technologies,Ltd. 2011-2015