

NL8048BC19-03

7.0" WVGA
Industrial use
[Features]

- **Portrait view compatible**※1
- **High contrast (800:1)**
- **16.77M/262K colors (LVDS RGB 8-bit/6-bit)**



Pixel	800(H) x 480(V)
Display area	152.4(H) x 91.44(V)mm 7.0 inches (18cm)
Display color	16,777,216 colors/262,144 colors
Pixel pitch	0.1905 (H) x 0.1905 (V)mm
Luminance	400 cd/m ² (typ.)
Contrast ratio	1,000:1 (typ.)
Viewing angle ※2	Up: 80°, Down: 80°, Left: 80°, Right: 80°
Response time ※3	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	3.4W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +80°C
Polarizer surface	Clear
Module size	170.0 (typ.) x 111.0 (typ.) x 9.0 (max.) mm
Weight	165g (typ.)
Backlight	LED backlight (Replaceable)
LED driver	Not provided

※1: Portrait view signals are to be prepared by a customer

※2: Contrast ratio ≥ 10:1

※3: Ton+Toff (10%←→90%)

※All information is subject to change without notice.

※Screen images are simulated.

<NLT Technologies web site>

Japanese <http://www.nlt-technologies.co.jp/jp>

English <http://www.nlt-technologies.co.jp/en>

Last update:11/2015

©NLT Technologies,Ltd. 2011-2015