



**SPECIFICATION**  
 Current Rating:1 Amp  
 Withstand Voltage:500V AC/Minute  
 Contact Resistance:20 Milliohms Max.  
 Insulation Resistance:1000 Megaohms Min.  
 Operation Temperature:-40°C~+105°C  
 Contact:Brass,Gold Flash Over Nickel  
 Insulator:PA6T+30%G.F.(UL94V-0),Black  
 RoHS Compliant

- PA V P 15 - 2 X XX C - H  
 (1)(2)(3)(4) (5) (6)(7) (8)  
 (1) PA:1.27X1.27mm Pin Header  
 (2) V:SMT Straight  
 (3) P:With Post  
 (4) 15:SMT Height 1.5mm  
 (5) 2: Dual Row  
 (6) XX:No. Of Position/Per Row  
 (7) C:With Cap  
 (8) H:RoHS Compliant

Pin	A	B	Pin	A	B
04	1.27	2.54	54	33.02	34.29
06	2.54	3.81	54	34.29	35.56
08	3.81	5.08	56	35.56	36.83
10	5.08	6.35	58	36.83	38.10
12	6.35	7.62	60	38.10	39.37
14	7.62	8.89	62	39.37	40.64
16	8.89	10.16	64	40.64	41.91
18	10.16	11.43	66	41.91	43.18
20	11.43	12.70	68	43.18	44.45
22	12.70	13.97	70	44.45	45.72
24	13.97	15.24	72	45.72	46.99
26	15.24	16.51	74	46.99	48.26
28	16.51	17.78	76	48.26	49.53
30	17.78	19.05	78	49.53	50.80
32	19.05	20.32	80	50.80	52.07
34	20.32	21.59	82	52.07	53.34
36	21.59	22.86	84	53.34	54.61
38	22.86	24.13	86	54.61	55.88
40	24.13	25.40	88	55.88	57.15
42	25.40	26.67	90	57.15	58.42
44	26.67	27.94	92	58.42	59.69
46	27.94	29.21	94	59.69	60.96
48	29.21	30.48	96	60.96	62.23
50	30.48	31.75	98	62.23	63.50
52	31.75	33.02	100	—	—

**AUK** A MEMBER OF AUK GROUP  
**太聯事業股份有限公司**  
**AUK CONTRACTORS CO., LTD.**

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.30 .XX ±0.20 .XXX ±0.10 .X' ±2'
PART No. PAVP15-2XXXC-H		MEI		
DRAWING No. PAVP15-2XXXC-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		
REV.	A0	UNIT mm	NO. REV.	

NEW RELEASE		HZF		06/04/2017	
REVISIONS		CHK		DATE	