



NOTES:

1. Rating: 300V 30 A
2. Insulation Withstands Voltage: AC 6000V at 1 minute.
3. Insulation Resistance: 500M Ω or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Value: 6 kgf-cm
6. Suitable Electric Wire: AWG 30~10
7. RoHS Compliance

PPACNV-4
PPACNV - series of terminal blocks
4 - modification for panel feed-through

Normal Geometric Tolerancing			
-	//	\equiv	\perp
0 to 100	±0.2	0 to 10	±0.25
over 100 to 150	0.3	over 10	±0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44

2	PPACN-4B	PA66	UL94-V0 GRAY
1	PPACNV-4A	PA66	UL94-V0 GRAY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	LWF	DATE	10.08.05	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	3:1 (:)		
APP.		DATE		PPACNV-4			
				DINKLE ENTERPRISE CO., LTD		NAME PPACNV-4	
REV.		CONTENT		CHK.		DATE	
						DWG NO. SP-03-PPACNV40	

REV.	CONTENT	CHK.	DATE