



Recommended P.C.B. Layout

△ SPECIFICATION
 Current Rating:5 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withsanding Voltage:2500V AC(1 Minute)
 Test Time=60s/1 PCS
 Wire Range:16~20 AWG
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature:
 250°C±10°C/5s Max.
 Insulator Body(Housing):Polyamide+G.F.(UL94V-0)
 Surface Of Solder Tails:Copper Alloy,Tin Plated
 RoHS Compliant

- △ TBX 35 XX C - XX - H
 (1) (2) (3) (4) (5) (6)
- (1) TBX:Terminal Block Spring Clamp,Screwfree Type
 - (2) 35:Pitch 3.5mm
 - (3) XX:No. Of Position
 - (4) C:Cable Outlet 45°
 - (5) XX:Insulator Color
 Blank:Gray
 GR:Green
 BK:Black
 BL:Blue
 - △ OR:Orange
 - (6) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°
PART No. TBX35XXC-XX-H		EMILY		
DRAWING No. TBX35XXC-XX-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY HAO		
REV.	A4	UNIT mm		

△ A4	Modify P/N Code	HZF	05/21/2015
△ A3	Modify Data	HZF	01/16/2014
△ A2	Modify Data	HZF	07/20/2013
△ A1	Add Color Orange	HZF	03/01/2011
△ A0	NEW RELEASE	HZF	01/15/2010
NO.REV.	REVISIONS	CHK	DATE