



NOTES:

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC STRENGTH :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

- 1.HOUSING MATERIAL :LEAD FREE POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE T=0.35mm FLAT PIN OR Ø0.46mm ROUND PIN.
- 3.PLATING :GOLD PLATING OVER NICKEL.
- 4.OPERATING :750 CYCLES MIN.
- 5.SHIELDING :0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.
- 6.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.Temperature Range : -40°C~+85°C
  - 2.Relative Humidity : 90~95% (40±2°C)
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

DIMENSIONS LIST	MM (INCH)	DFTD: DATE: 08.7.1	Trxcom ShenZhen Trxcom Electronics Co.,Ltd
	TOLERANCES EXCEPT AS NOTED	CHKD: DATE: 08.7.1	
	MM	APPRV: DATE: 08.7.1	
	±		
0.10 ± 0.10		TITLE	2X6 SHIELDED WITH EMI WITH LED
0.20 ± 0.15		/PART NO.	TRJE67011ADNL
0.50 ± 0.075		SCALE: 1:1	DO NOT SCALE DRAWING
ANGLES ± 0.5°			SHEET 1 OF 1
THIRD ANGLE PROJECTION			

H  
G  
F  
E  
D  
C  
B  
A