



SPECIFICATION

Current:1.5A Max.
 Voltage:30V Max.
 Withstanding Voltage:500V AC
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operating Temperature:-55°C~+85°C
 Housing:LCP+30%G.F.,Black
 Contact:C2680R-H
 Shell:SPCC,Nickel Plated
 Mating Force:35N Max.
 Withdrawal Force:10N Min.
 Durability:1500 Cycles Min.
 RoHS Compliant

USB D 1X04 PW X C - BK - SXX - R6H - H
 (1) (2) (3) (4) (5) (6) (7) (8) (9) (10)

- (1) USB:USB Series
- (2) D:Dent Type
- (3) 1X04:A Type
- (4) PW:Male SMT Right Angle
- (5) X:Without Kink
- (6) C:With Mylar
- (7) BK:Black
- (8) SXX>Contact Finish
 Blank:Gold Flash On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 S30:Gold Plated 30u" On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
- (9) R6H:Tape&Reel 600 PCS/Reel
- (10) H:RoHS Compliant

Recommended P.C.B. Layout

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 X.° ±5° .X ±0.20 .X° ±3° .XX ±0.15
PART No.		MEI		
DRAWING No.		CHECKED BY		
SCALE		HAO		
NONE		DRAWING BY		UNIT mm
REV.		AO		

NO.	REV.	DESCRIPTION	CHK	DATE
△ A0		NEW RELEASE	HZF	07/13/2015
		REVISIONS		