




Clamp Spring - Spring type terminal blocks / WK series



WKR508A



Pitch: 5.08mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Conductor cross-section, solid (AWG/ mm ²)	28~12 / 0.5~2.5	
Conductor cross-section, flexible (AWG/ mm ²)	28~12 / 0.5~2.5	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / 4 KV	
Wire strip length	5~6mm	
Single Pole	Cat. No.	
	WKR508A-01X	
End Cover	WKR500AC	



Optional color	Cat. No.
	WKR508A-01X
	WKR508A-01X-GN
	WKR508A-01X-RD
	WKR508A-01X-BL
	WKR508A-01X-BK
	WKR508A-01X-OR
Pole	Cat. No.
02	WKR508A-02P
03	WKR508A-03P
04	WKR508A-04P
05	WKR508A-05P
06	WKR508A-06P
07	WKR508A-07P
08	WKR508A-08P
09	WKR508A-09P
10	WKR508A-10P
11	WKR508A-11P
12	WKR508A-12P
:	:
:	:
Optional color	Cat. No.
	WKR508A-XXP
	WKR508A-XXP-GN
	WKR508A-XXP-RD
	WKR508A-XXP-BL
	WKR508A-XXP-BK
	WKR508A-XXP-OR

TEL: +886-2-2908-0614**FAX:** +886-2-2908-8549**E-mail:** info@dinkle.com.tw