


Clamp Spring - Spring type terminal blocks / WK series

WKV250A



Pitch: 2.50mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	4A	6A
Conductor cross-section, solid (AWG/ mm ²)	28~20 / 0.5	
Conductor cross-section, flexible (AWG/ mm ²)	0.5	
Rated surge voltage (UL/IEC/Max.)	1.6 / 1.25 / 2 KV	
Wire strip length	5~6mm	
Single Pole	Cat. No.	
	WKV250A-01X	
End Cover	WKV250AC	



Optional color	Cat. No.
	WKV250A-01X
	WKV250A-01X-GN
	WKV250A-01X-RD
	WKV250A-01X-BL
	WKV250A-01X-BK
	WKV250A-01X-OR

Pole	Cat. No.
02	WKV250A-02P
03	WKV250A-03P
04	WKV250A-04P
05	WKV250A-05P
06	WKV250A-06P
07	WKV250A-07P
08	WKV250A- 08P
09	WKV250A- 09P
10	WKV250A-10P
11	WKV250A-11P
12	WKV250A-12P
:	:
:	:

Optional color	Cat. No.
	WKV250A-XXP
	WKV250A-XXP-GN
	WKV250A-XXP-RD
	WKV250A-XXP-BL
	WKV250A-XXP-BK
	WKV250A-XXP-OR

TEL: +886-2-2908-0614**FAX:** +886-2-2908-8549**E-mail:** info@dinkle.com.tw