



SPECIFICATION
 Current Rating: 1 Amps
 Withstand Voltage: 500V AC
 Contact Resistance: 20 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Operation Temperature: -40°C ~ +105°C
 Contact: Phosphor Bronze, Gold Flash Over Nickel
 Insulator: PA6T (UL94V-0), Black
 RoHS Compliant

YA D 43 - 2 X XX - H H
 (1) (2) (3) (4) (5) (6) (7)

- (1) YA: 1.27x1.27mm Female Header
- (2) D: DIP Straight
- (3) 43: 4.3mm Insulator Height
- (4) 2: Dual Row
- (5) XX: No. Of Position/Per Row
- (6) H: Withstand High Temperature Soldering
- (7) H: RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.25 X.* ±2" .X ±0.20 .X* ±1.5" .XX ±0.15 .XX* ±1" .XXX ±0.10 .XXX* ±0.5"
PART No. YAD43-2XXX-HH		MEI		
DRAWING No. YAD43-2XXX-HH		CHECKED BY HZF		
SCALE		DRAWING BY CYP		
SCALE	NONE	REV.	A0	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A0		NEW RELEASE	HZF	09/28/2015